



Robe iESprite LTL

Robe iESprite LTL

A compact, powerful WashBeam/follow-spot luminaire using a patented iSE-TE™ 750W LED engine, delivering up to 260,000 lx @ 5m with a 3°-57° zoom range, suitable for concert touring, theatrical, and broadcast productions indoors and outdoors.



Physical

Physical size	Height: 760 mm (29.92") / Width: 458 mm (18.03") / Depth: 289 mm (11.37") - head in vertical position
Item weight	37.5 kg

Electrical

Rated power	950 W
Input power	100-240 V, 50/60 Hz
Power connection	Neutrik powerCON TRUE1

Mounting Options

Hanging type	Horizontally or vertically mountable; 5 pairs of 1/4-turn locking points; 2x Omega adaptors with 1/4-turn quick locks
Freestanding	No
Expo LX	260,000 lx @ 5 m (XP engine) / 140,000 lx @ 5 m (HCF engine)

Optical

Light source	iSE-TE™ 750W XP White LED Engine or iSE-TE™ 750W HCF White LED Engine (Patented)
Beam angle	3° - 57° (standard optical range) / 2° - 57° (optical zoom + iris) / 0.7° - 2° (long-throw mode)
Colour temperature	6,700 K (XP engine) / 6,000 K (HCF engine); variable CTO: 3,000 K - 6,700 K
CRI	70 (XP engine, with remotely selectable filters for CRI 80 and CRI 90) / 96 (HCF engine)

DMX / Control

DMX mode	1 (single protocol mode)
DMX channels	53 (control channels)

DMX / Control

DMX connection	IP65 Locking 3-pin & 5-pin XLR connectors
----------------	---

Environmental

IP rating	IP65
-----------	------

Accessories

Accessories	User Manual, Omega Adapter CL-regular (2 pcs), Power cord with powerCON TRUE1 In connector, Balancing Weight Cover for CamFit
-------------	---

Information Links

Information links	https://cdn.aws.robe.cz/print/en_product_6372.pdf
Manufacturer link	https://www.robe.cz/