



Hollyland Wireless Video 4k Transmitter - Py

Hollyland Wireless Video 4k Transmitter - Pyro

Professional 4K wireless video transmission system with one transmitter connecting to unlimited receivers, supporting true 4K60 transmission, Focus Mode with latency as low as 20ms, and HDMI/SDI flexibility for on-set monitoring and production workflows.

Physical

Physical size	124.5 × 80 × 34.9 mm (L × W × H)
Item weight	0.32

Input / Outputs

Inputs / outputs	HDMI 2.0 input, HDMI 2.0 loop-out (transmitter); HDMI 2.0 output, 3G SDI input/output, USB-C, DC barrel connector (2.0 mm)
Port count	Transmitter: 1× HDMI in, 1× HDMI loop-out, 1× SDI in, 1× USB-C, 1× DC in; Receiver: 1× HDMI out, 1× SDI out, 1× USB-C, 1× DC in



Electrical

Rated power	Transmitter: 11W (non-broadcast), 14W (broadcast); Receiver: 7W
Input power	Transmitter: 6-16V DC or 6.8-8.4V battery; Receiver: 6-16V DC or 11.8-16.8V battery

Accessories

Accessories	4 antennas (2.4 GHz and 5 GHz), 1 hot shoe mount, 1 USB-C OTG adapter, 12V/2A power adapter
-------------	---

Information Links

Information links	https://www.hollyland.com/product/pyro-ultra https://store.hollyland.com/products/pyro-ultra
Manufacturer link	https://www.hollyland.com