



ROBE LTX FS

ROBE LTX FS

High-output LED WashBeam with integral RoboSpot camera, delivering up to 55,000 lm and 355,000 lx @ 5m with long-throw follow-spot capability for live concert touring, indoors or out.

Physical

Physical size	904 mm H × 480 mm W × 335 mm D (head in vertical position)
Item weight	49 kg

Electrical

Rated power	1250W
Input power	100-240 V, 50/60 Hz
Power connection	IP65 Neutrik powerCON TRUE1



Mounting Options

Hanging type	5 pairs of 1/4-turn locking points; mounting positions 0°, 32°, 90°
Freestanding	Universal operating position
Expo LX	355000 @ 5m

Optical

Light source	iSE-TE™ 1000W XP White LED Engine
Beam angle	3.5° - 52° (standard); 2° - 52° (with iris); 0.7° - 2° (long-throw mode)
Colour temperature	6700 K
CRI	70 (with remotely selectable filters for CRI 80 and CRI 90)

DMX / Control

DMX mode	1
DMX channels	54
DMX connection	IP65 Locking 3-pin & 5-pin XLR connectors

Environmental

IP rating	IP65
-----------	------

Accessories

Accessories	User Manual, 2x Omega Adaptor CL-regular, Power cord with powerCON TRUE1 connector, 2° Beam reductor, RoboSpot Camera, Balancing Weight Cover for CamFit
-------------	--

Information Links

Information links	https://cdn.aws.robe.cz/print/en_product_5617.pdf
Manufacturer link	https://www.robe.cz